


## Reelcraft LC series

Profitable hose reel available in powdercoated or stainless steel version. Robust, springwound, suitable for water and air applications.

Mounted on a baseplate with hoseguide in the adjustable guide arm.



Model	LC serie
	mm.
A	521
B	492
C	121
D	76
E	206



Springwound, with/without hose  
Maximum temperature +65 °C.

### Powdercoat models with hose:

Complete with durable pvc hose, suitable for water and air.

article code	model	inlet fem "	Outlet fem "	Ø hose mm.	length mtr.	WP bar	weight kg.
9LC650OLP	LC650 OLP-70	1/4	1/4	10	15	21	17
9LC670OLP	LC670 OLP-70	1/4	1/4	10	21	21	20
9LC850OLP	LC850 OLP-70	1/2	1/2	13	15	21	19
9LC870OLP	LC870 OLP-70	1/2	1/2	13	21	21	22

### Poedercoat modellen zonder slang:

article code	model	inlet fem "	Outlet fem "	Ø hose mm.	length mtr.	WP bar	weight kg.
9LC607OLP	LC607 OLP-70	1/4	1/4	10	20	21	16
9LC807OLP	LC807 OLP-70	1/2	1/2	13	20	21	16



### RVS modellen zonder slang:

article code	model	inlet fem "	Outlet fem "	Ø hose mm.	length mtr.	WP bar	weight kg.
9LC607OLS	LC607 OLS-70	1/4	1/4	10	20	21	16
9LC807OLS	LC807 OLS-70	1/2	1/2	13	20	21	16