

Stoomkoppelingen EN14423

Koppelingen voor stoomslang uitgevoerd volgens EN14423 (DIN2826).
 Werkdruk 18 bar voor verzadigde stoom tot 210 °C. of water tot 120 °C.

BSPT buitendraad

artikelnr. staal	artikelnr. rvs	artikelnr. messing	draad "	tule mm.
4740112	4740112R	4740112M	1/2	13
4740119	4740119R	4740119M	3/4	19
4740125	4740125R	4740125M	1	25
4740132	4740132R	4740132M	1 1/4	32
4740138	4740138R	4740138M	1 1/2	38
4740150	4740150R	4740150M	2	50



BSPT binnendraad

artikelnr. staal	artikelnr. rvs	artikelnr. messing	draad "	tule mm.
4741112	4741112R	4741112M	1/2	13
4741119	4741119R	4741119M	3/4	19
4741125	4741125R	4741125M	1	25
4741132	4741132R	4741132M	1 1/4	32
4741138	4741138R	4741138M	1 1/2	38
4741150	4741150R	4741150M	2	50



Stoomklemschalen EN14423

Tweedelige klemschaal voor stoomslang, met inbusbouten en moeren volgens EN14423. Rvs klemschalen worden geleverd met rvs bouten en moeren.

artikelnr. messing	artikelnr. rvs	slangmaat mm.	klembereik mm.
4722013	4722013R	13 x 6,0	24 - 26
4722019	4722019R	19 x 7,0	32 - 34
4722025	4722025R	25 x 7,5	39 - 41
4722032	4722032R	32 x 8,0	47 - 50
4722038	4720038R	38 x 8,0	53 - 56
4722050	4722050R	50 x 9,0	67 - 69



Stoomkoppelingen US, systeem Boss

Systeem Boss stoomkoppelingen.

Werkdruk 18 bar voor verzadigde stoom tot 210 °C. of water tot 120 °C.

BSPT buitendraad

artikelnr. staal	draad "	tule mm.
4740012	1/2	13
4740019	3/4	19
4740025	1	25
4740032	1 1/4	32
4740038	1 1/2	38
4740050	2	50



BSPT binnendraad

artikelnr. staal	draad "	tule mm.
4741012	1/2	13
4741019	3/4	19
4741025	1	25
4741032	1 1/4	32
4741038	1 1/2	38
4741050	2	50



Stoomklempaten US

Tweedelige stalen klemplaat voor stoomslang. Geschikt voor US koppelingen (systeem Boss)

artikelnr.	slangmaat mm.	klembereik mm.
4723013	13 x 6,0	24 - 27
4723019	19 x 7,5	30 - 33
4723020	19 x 9,0	33 - 38
4723025	25 x 8,5	39 - 43
4723032	32 x 9,0	45 - 53
4723038	38 x 10,0	55 - 60
4723050	50 x 10,0	63 - 71

